






VULCANIZADOS TRANCHO, S.A.

C/ Bazán nº 6-8 P.I Bankuni3n I 33211 Tremañes Gij3n Asturias
 Tel. 985 345 773 M3vil 679 48 48 55 / 57 www.trancho.com



Raccords à cames sécurisés / Racor Camelock con seguridad

● Química y Petroquímica

		Diam. raccord <i>Diam. racor</i>	Diam. douille <i>Diam. espiga</i>	Code article <i>Referencia</i>	Nouveau <i>Nuevo</i>	Trelleborg Design	Tuyau <i>Manguera</i>
Raccords à cames sécurisés / Racor Camelock con seguridad							
 <p>Coupleur sécurisé. Tarauté. Femelle. BSPP. Type D. Avec joint de filetage. EN 14420-7. <i>Acoplador seguro. Taladrado. Hembra. BSPP. Con junta roscada. EN 14420-7.</i></p>	Inox 316 Acero inoxidable 316	20	3/4"	SAFD19	✓		●
		25	1"	SAFD25	✓		●
		32	1-1/4"	SAFD32	✓		●
		40	1-1/2"	SAFD40	✓		●
		50	2"	SAFD50	✓		●
		65	2-1/2"	SAFD65	✓		●
		80	3"	SAFD80	✓		●
 <p>Coupleur sécurisé. A douille lisse. A collerette. EN 14420 / DIN 2817. <i>Acoplador seguro. Con cuello liso. Con cuello. EN 14420 / DIN 2817.</i></p>	Inox 316 Acero inoxidable 316	20		SAFDL19	✓		●
		25		SAFDL25	✓		●
		32		SAFDL32	✓		●
		40		SAFDL40	✓		●
		50		SAFDL50	✓		●
		65		SAFDL65	✓		●
		80		SAFDL80	✓		●
 <p>Coupleur sécurisé. A souder. BW. <i>Acoplador seguro. Para soldar. BW.</i></p>	Inox 316 Acero inoxidable 316	20	26.7	SAFBW19	✓		●
		25	33.4	SAFBW25	✓		●
		32	42.2	SAFBW32	✓		●
		40	48.3	SAFBW40	✓		●
		50	60.3	SAFBW50	✓		●
		65	76.1	SAFBW65	✓		●
		80	88.9	SAFBW80	✓		●
100	114.3	SAFBW100	✓		●		